



Synchronous PM Motor and Drive Packages - IES2

PM MOTOR WITH INTEGRATED DRIVE - IES2

- Maximum integration for increasingly performance
- IE5 motor + IE2 VFD
- Combination of AC motor's reliability and Brushless Servomotor's performance

HP Integral
Smart Flow Plus
solutions to meet your needs

IES2

TECHNICAL DATA

Motor Type

HPI 112 3600 317_Flow 15 kW - 3600 rpm | Drive three-phase - 500-600V

PERFORMANCE DATA

Package Type	HPI 112 3600 317_Flow
Rated Speed rpm	3600
Rated Power kW	15
Rated Power HP	20
Rated Torque Nm	39.8
Peak Torque Nm	59.7
Rated Current Arms	31.7
Peak Current Arms	47.5
Rated input current 380Vac Arms	31.5
Rated input current 480Vac Arms	25.0
Torque Constant Nm/A	1.26
HPI Weight kg	38.5
Motor Efficiency IE code	IE5

Drive Type	Flow
Drive Efficiency IE code	IE2
HPI Efficiency IE code	IES2
HPI Efficiency ? %	94.5

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6208 2Z
Bearings NDE	6306 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)

Electrical Data

Supply Voltage	400V - 50Hz
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1001 m.a.s.l.

Drive Data

Drive Type	Flow
Supply Voltage	three-phase
Drive Voltage	500-600V
Safety Function	STO/PLC
Drive Torque	variable
Fieldbus	BACnet MS/TP; Modbus RTU
Inputs	3 Digital (+3 optional); 2 Analog / Digital selectable
Outputs	2 Analog / Digital; 2 Relays (+3 optional)

