

Synchronous PM Motor and Drive Packages - IES2

PM MOTOR AND COMBINED DRIVE - IES2



- Plug & Play solution
- Total speed control
- IP20 or IP66 / NEMA 4X outdoor
- Three package configurations

HP Combi
Smart Flow Plus
solutions to meet your needs

IES2 

TECHNICAL DATA

Motor Type

HPC 132 3600_Plus_IP66 15 kW - 3600 rpm | Drive three-phase - 500-600V

PERFORMANCE DATA

Package Type	HPC 132 3600_Plus_IP66
Rated Speed rpm	3600
Rated Power kW	15
Rated Power HP	20
Rated Torque Nm	39.8
Peak Torque Nm	119.4
Voltage Constant Vs	0.73
Torque Constant Nm/A	1.26
B.E.M.F. @ rated speed Vrs	272
Rated Current Arms	31.7
Motor Efficiency IE code	IE5
Motor Efficiency η %	93.7
Motor Weight Kg	55

Drive Type	Plus
Drive Size	4
Drive Efficiency IE code	IE2
HPC Efficiency IE code	IES2
HPC Efficiency ? %	92.7

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6309 2Z
Bearings NDE	6208 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)

Electrical Data

Motor Supply Voltage	400V - 50Hz
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1000 m.a.s.l.

Drive Data

Drive Type	Plus
Drive Size	4
Supply Voltage	three-phase
Drive Voltage	500-600V
Safety Function	STO/PLC
Drive Torque	constant/variable
Fieldbus	CANopen; Modbus RTU

Inputs	3 Digital (+3 optional); 2 Analog / Digital selectable
Outputs	2 Analog / Digital; 2 Relays (+3 optional)
Degree of Protection	IP 66