



Synchronous PM Motors - IE6/IE5

ULTRA PREMIUM EFFICIENCY MOTORS - IE5

- IE5 Ultra Premium Efficiency
- Combination of AC motor's reliability and Brushless Servomotor's performance
- High runners always in stock

IE5 

TECHNICAL DATA

Motor Type

IE5 HPS 132 3000 318 15 kW - 3000 rpm - 400V - 50Hz

PERFORMANCE DATA

| | |
|---------------------------------------|----------------------|
| Type | IE5 HPS 132 3000 318 |
| Rated Speed rpm | 3000 |
| Rated Power kW | 15 |
| Rated Power HP | 20 |
| Rated Torque Nm | 47.8 |
| Peak torque Nm | 143.3 |
| Voltage constant Vs | 0.87 |
| Torque constant Nm/A | 1.5 |
| B.E.M.F. @ rated speed Vrs | 272 |
| Rated current Arms | 31.8 |
| Efficiency IE code | IE5 |
| Efficiency η % | 93.7 |
| Weight Kg | 55 |

Mechanical Data

| | |
|-----------------------------|-------------------------------|
| Design | ALUMINIUM |
| Degree of protection | IP 55 |
| Bearings DE | 6309 2Z |
| Bearings NDE | 6208 2Z |
| Lubrication grease | low & high temperature grease |
| Regreasing device | permanent lubrication |
| Cooling | IC 411 |
| Vibration Level | A (normal) |

Electrical Data

| | |
|------------------------------|----------------|
| Supply Voltage | 400V - 50Hz |
| Duty type | S1 |
| Insulation class | F |
| Direction of rotation | bidirectional |
| Ambient temperature | -15°C / +40 °C |
| Altitude | 1000 m.a.s.l. |