



Synchronous PM Motors - IE6/IE5

ULTRA PREMIUM EFFICIENCY MOTORS - IE5

- IE5 Ultra Premium Efficiency
- Combination of AC motor's reliability and Brushless Servomotor's performance
- High runners always in stock

IE5 

TECHNICAL DATA

Motor Type

IE5 HPS 132 3000 467 22 kW - 3000 rpm - 400V - 50Hz

PERFORMANCE DATA

Type	IE5 HPS 132 3000 467
Rated Speed rpm	3000
Rated Power kW	22
Rated Power HP	30
Rated Torque Nm	70.0
Peak torque Nm	210.1
Voltage constant Vs	0.87
Torque constant Nm/A	1.5
B.E.M.F. @ rated speed Vrs	272
Rated current Arms	46.7
Efficiency IE code	IE5
Efficiency η %	94.4
Weight Kg	67

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6309 2Z
Bearings NDE	6208 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)

Electrical Data

Supply Voltage	400V - 50Hz
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1000 m.a.s.l.