




Synchronous PM Motors - IE6/IE5

HYPER EFFICIENCY MOTORS - IE6

- IE6 Hyper Efficiency
- The revolution in industrial efficiency
- Power, compactness and efficiency

IE6 

TECHNICAL DATA

Motor Type

IE6 HPS 71 3600 16 0.75 kW - 3600 rpm - 400V - 50Hz

PERFORMANCE DATA

Type	IE6 HPS 71 3600 16
Rated Speed rpm	3600
Rated Power kW	0.75
Rated Power HP	1
Rated Torque Nm	2.0
Peak torque Nm	6.0
Voltage constant Vs	0.73
Torque constant Nm/A	1.26
B.E.M.F. @ rated speed Vrs	272
Rated current Arms	1.6
Efficiency IE code	IE6
Efficiency η %	87.3
Weight Kg	5.2

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6205 2Z
Bearings NDE	6303 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6205 2Z
Bearings NDE	6303 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)

Electrical Data

Supply Voltage	400V - 50Hz
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1000 m.a.s.l.
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1000 m.a.s.l.