



AC Three-phase Motors - IE4/IE3/IE2/IE1

HIGH EFFICIENCY MOTORS - IE2

- Customisation at all levels



TECHNICAL DATA

Motor Type

AMMEHE 71Z XA4 - 0.18 kW - 4 poles - 230V - 50Hz

PERFORMANCE DATA

Type	AMMEHE 71Z XA
Poles	4
kW	0.18
HP	0.25
rpm	1390
Mn Nm	1.2
η 100%	64.70
cos Phi	0.98
I_N 230V	1.2
I_A/I_N	2.7
M_A/M_N	2.0
M_K/M_N	1.5
$J \cdot 10^{-3} \text{ kgm}^2$	1.08
kg	8.5

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	42

Electrical Data

Voltage	230V - 50Hz
Connection	230V
Running Capacitor Microf	10
Starting Capacitor Microf	30 - 36
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.