



AC Three-phase Motors - IE4/IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Reliability and efficiency in a well-designed robust package
- Extensive customization options ensure motors match application needs



TECHNICAL DATA

Motor Type

AM 132M DA4 - 11.0 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AM 132M DA
Poles	4
kW	11.0
HP	15
rpm	1450
Mn Nm	72.4
η 50%	84.7
η 75%	86.5
η 100%	87.6
cos Phi	0.79
I _N 400V	23.0
I _N 380-420V	23.5
I _A /I _N	8.2
M _A /M _N	2.6

M_S/M_N	2.4
M_K/M_N	3.7
$J \cdot 10^{-3} \text{ kgm}^2$	31.5
kg	65.0

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6208/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	59

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.