



AC Three-phase Motors - IE4/IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Reliability and efficiency in a well-designed robust package
- Extensive customization options ensure motors match application needs



TECHNICAL DATA

Motor Type

AM 132M ZA8 - 3.0 kW - 8 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AM 132M ZA
Poles	8
kW	3.0
HP	4
rpm	710
Mn Nm	40.4
η 50%	81.3
η 75%	82.0
η 100%	79.8
cos Phi	0.67
I _N 400V	8.1
I _N 380-420V	8.4
I _A /I _N	3.6
M _A /M _N	1.7

M_S/M_N	1.6
M_K/M_N	1.9
$J \cdot 10^{-3} \text{ kgm}^2$	37.4
kg	54.5

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6208/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	52

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.