



AC Three-phase Motors - IE4/IE3/IE2/IE1

SUPER PREMIUM EFFICIENCY MOTORS - IE4/CURUS

- Wide range from 0.75 to 200kW
- Total reliability and longevity in a well-engineered package
- Enhanced designs to meet today's challenges and market needs



TECHNICAL DATA

Motor Type

AMQH 80Z AA44 - 0.75 kW - 4 poles - 460V - 60Hz / 575V - 60Hz

PERFORMANCE DATA

Type	AMQH 80Z AA4
Poles	4
kW	0.75
HP	1
rpm	1745
Mn Nm	4.1
η 50%	80.9
η 75%	83.6
η 100%	85.5
cos Phi	0.75
I_N 400V	-
I_N 460V	1.5
I_N 575V	1.2

I_A/I_N	8.9
M_A/M_N	4.3
M_S/M_N	3.8
M_K/M_N	4.5
$J \cdot 10^{-3} \text{ kgm}^2$	2.5
kg	11.0

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6204/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	48

Electrical Data

Voltage	460V - 60Hz / 575V - 60Hz
Connection	
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.