



AC Three-phase Motors - IE4/IE3/IE2/IE1

SUPER PREMIUM EFFICIENCY MOTORS - IE4/CURUS

- Wide range from 0.75 to 200kW
- Total reliability and longevity in a well-engineered package
- Enhanced designs to meet today's challenges and market needs



TECHNICAL DATA

Motor Type

AMQH 112M BA44 - 3 kW - 4 poles - 460V - 60Hz / 575V - 60Hz

PERFORMANCE DATA

Type	AMQH 112M BA4
Poles	4
kW	3
HP	4
rpm	1770
Mn Nm	16.2
η 50%	88.1
η 75%	90.0
η 100%	91.0
cos Phi	0.77
I_N 400V	-
I_N 460V	5.4
I_N 575V	4.3

I_A/I_N	10.0
M_A/M_N	3.4
M_S/M_N	2.1
M_K/M_N	4.4
$J \cdot 10^{-3} \text{ kgm}^2$	17.4
kg	38.9

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6306/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	53

Electrical Data

Voltage	460V - 60Hz / 575V - 60Hz
Connection	
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.