



AC Three-phase Motors - IE4/IE3/IE2/IE1

PREMIUM EFFICIENCY MOTORS - IE3/CURUS

- IE3 Premium Efficiency compliant since 2010
- Total reliability and longevity in a well-engineered package
- Enhanced designs to meet today's challenges and market needs



TECHNICAL DATA

Motor Type

AMPE 225S PG4 - 37 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPE 225S PG
Poles	4
kW	37
HP	50
rpm	1485
Mn Nm	237.9
η 50%	92.0
η 75%	93.9
η 100%	93.9
cos Phi	0.86
I_N	66.1
I_A/I_N	7.4
M_A/M_N	2.0
M_S/M_N	1.9

M_K/M_N	2.3
J 10⁻³ kgm²	406
kg	328

Mechanical Data

Design	Cast iron
Degree of protection	IP 55
Bearings DE/NDE	6313 C3
Lubrication grease	low & high temperature grease
Regreasing device horizontal	4.600 hours
Regreasing device vertical	4.600 hours
Grease Quantity	25 gr
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	76

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.