



AC Three-phase Motors - IE4/IE3/IE2/IE1

HIGH EFFICIENCY MOTORS - IE2/CURUS

- Total reliability and longevity in a well-engineered package
- Extensive customization options ensure motors match application needs



TECHNICAL DATA

Motor Type

AMHE 63Z CA2 - 0.37 kW - 2 poles - 400V - 50Hz / 460V - 60Hz

PERFORMANCE DATA

Type	AMHE 63Z CA
Poles	2
kW	0.37
HP	0.5
rpm	2750
Mn Nm	1.3
η 50%	59.1
η 75%	66.2
η 100%	69.5
cos Phi	0.69
I_N	1.1
I_A/I_N	4.6
M_A/M_N	3.4

M_S/M_N	3.3
M_K/M_N	3.4
J 10⁻³ kgm²	0.20
kg	4.4

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6202/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	49

Electrical Data

Voltage	400V - 50Hz / 460V - 60Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.