



AC Three-phase Motors - IE4/IE3/IE2/IE1

HIGH EFFICIENCY MOTORS - IE2/CURUS

- Total reliability and longevity in a well-engineered package
- Extensive customization options ensure motors match application needs



TECHNICAL DATA

Motor Type

AMHE 80Z CA2 - 1.5 kW - 2 poles - 400V - 50Hz / 460V - 60Hz

PERFORMANCE DATA

Type	AMHE 80Z CA
Poles	2
kW	1.5
HP	2.0
rpm	2880
Mn Nm	5.0
η 50%	80.5
η 75%	82.1
η 100%	82.4
cos Phi	0.78
I_N	3.4
I_A/I_N	7.8
M_A/M_N	3.5

M_S/M_N	3.4
M_K/M_N	3.6
J 10⁻³ kgm²	1.1
kg	13.5

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6204/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	60

Electrical Data

Voltage	400V - 50Hz / 460V - 60Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.