



AC Three-phase Motors - IE4/IE3/IE2/IE1

HIGH EFFICIENCY MOTORS - IE2/CURUS

- Total reliability and longevity in a well-engineered package
- Extensive customization options ensure motors match application needs



TECHNICAL DATA

Motor Type

AMHE 132M CA4 - 9.2 kW - 4 poles - 400V - 50Hz / 460V - 60Hz

PERFORMANCE DATA

Type	AMHE 132M CA
Poles	4
kW	9.2
HP	12.5
rpm	1460
Mn Nm	60.3
η 50%	90.2
η 75%	90.6
η 100%	89.3
cos Phi	0.83
I_N	18.0
I_A/I_N	8.2
M_A/M_N	2.6

M_S/M_N	2.4
M_K/M_N	3.7
J 10⁻³ kgm²	33.0
kg	65.0

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6208/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	59

Electrical Data

Voltage	400V - 50Hz / 460V - 60Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.