



Brake Motors - IE3/IE2/IE1

HIGH EFFICIENCY MOTORS - IE2

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMHEBY 132M ZA2 - 9.2 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMHEBY 132M ZA
Poles	2
kW	9.2
HP	12.5
rpm	2920
Mn Nm	30.1
η 50%	88.4
η 75%	89.9
η 100%	90
cos Phi	0.87
I_N	16.9
I_A/I_N	8.8
M_A/M_N	3.2
M_K/M_N	3.8

J 10 ⁻³ kgm ²	18.5
Mb max Nm	75(150) ²
zL 1) c/h	555
kg	78

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6208/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	72

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.