



Brake Motors - IE3/IE2/IE1

HIGH EFFICIENCY MOTORS - IE2

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMHEBY 160L TA2 - 22 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMHEBY 160L TA
Poles	2
kW	22
HP	30
rpm	2935
Mn Nm	71.6
η 50%	91
η 75%	91.7
η 100%	91.5
cos Phi	0.9
I_N	38.6
I_A/I_N	8.3
M_A/M_N	3
M_K/M_N	3.7

J 10 ⁻³ kgm ²	59
Mb max Nm	150(250) ²
zL 1) c/h	370
kg	137

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6309/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	74

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.