



Brake Motors - IE3/IE2/IE1

HIGH EFFICIENCY MOTORS - IE2

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMHEBY 71Z CA4 - 0.55 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

| | |
|------------------------------------|-------------------|
| Type | AMHEBY 71Z CA |
| Poles | 4 |
| kW | 0.55 |
| HP | 0.75 ¹ |
| rpm | 1410 |
| Mn Nm | 3.8 |
| η 50% | 71.5 |
| η 75% | 75.5 |
| η 100% | 77.1 |
| cos Phi | 0.71 |
| I_N | 1.5 |
| I_A/I_N | 3.6 |
| M_A/M_N | 2.4 |
| M_K/M_N | 2.4 |

| | |
|------------------------------------------|------|
| J 10⁻³ kgm² | 1.11 |
| Mb max Nm | 7.5 |
| zL 1) c/h | 6900 |
| kg | 10.4 |

Mechanical Data

| | |
|-------------------------------------|-------------------------------|
| Design | Aluminium |
| Degree of protection | IP 55 |
| Bearings DE/NDE | 6203/2Z |
| Lubrication grease | low & high temperature grease |
| Regreasing device horizontal | permanent lubrication |
| Regreasing device vertical | permanent lubrication |
| Cooling | IC 411 |
| Vibration Level | A (normal) |
| Noise Lpa db(A) | 42 |

Electrical Data

| | |
|------------------------------|----------------|
| Voltage | 400V - 50Hz |
| Connection | ?/Y 230/400V |
| Duty type | S1 |
| Thermal protection | na |
| Insulation class | F |
| Direction of rotation | bidirectional |
| Ambient temperature | -20°C / +40 °C |
| Altitude | 1000 m.a.s.l. |