



Brake Motors - IE3/IE2/IE1

HIGH EFFICIENCY MOTORS - IE2

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMHES 132S ZA2 - 5.5 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMHES 132S ZA
Poles	2
kW	5.5
HP	7.5
rpm	2900
Mn Nm	18.1
η 50%	86
η 75%	88
η 100%	87.9
cos Phi	0.89
I_N	10.2
I_A/I_N	7.3
M_A/M_N	2.7
M_K/M_N	3.2

J 10⁻³ kgm²	17
Mb max Nm	30
zL ¹⁾ c/h	480
kg	52

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6208/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	72

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V or ?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.