



Brake Motors - IE3/IE2/IE1

PREMIUM EFFICIENCY MOTORS - IE3

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMPEBZ 160L DA4 - 22 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPEBZ 160L DA
Poles	4
kW	22
HP	30
rpm	1470
Mn Nm	143.9
η 50%	92.4
η 75%	93.1
η 100%	93.0
cos Phi	0.76
I_N	45.0
I_A/I_N	8.0
M_A/M_N	2.2
M_K/M_N	3.0

J 10⁻³ kgm²	120
Mb max Nm	250
zL ¹⁾ c/h	550
kg	168

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6309/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	62

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.