



Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMBY 71Z CA2 - 0.75 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBY 71Z CA
Poles	2
kW	0.75
HP	1
rpm	2800
Mn Nm	2.56
η 50%	58.9
η 75%	65.7
η 100%	72.6
cos Phi	0.76
I_N 400 V	2
I_N 380-400 V	2.1
I_A/I_N	5.2
M_A/M_N	3.1

M_K/M_N	3.1
$J \cdot 10^{-3} \text{ kgm}^2$	0.57
$M_b \text{ max Nm}$	7.5
$zL^{-1} \text{ c/h}$	4500
kg	10.3

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	52

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.