



### Brake Motors - IE3/IE2/IE1

### STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



## TECHNICAL DATA

**Motor Type** AMBY 112M BA2 - 5.5 kW - 2 poles - 400V - 50Hz

## PERFORMANCE DATA

<b>Type</b>	AMBY 112M BA
<b>Poles</b>	2
<b>kW</b>	5.5
<b>HP</b>	7.5
<b>rpm</b>	2900
<b>Mn Nm</b>	18.11
$\eta$ 50%	83.6
$\eta$ 75%	84.7
$\eta$ 100%	85
<b>cos Phi</b>	0.86
<b>I<sub>N</sub> 400 V</b>	10.9
<b>I<sub>N</sub> 380-400 V</b>	11.2
<b>I<sub>A</sub>/I<sub>N</sub></b>	7.8
<b>M<sub>A</sub>/M<sub>N</sub></b>	3.5

<b><math>M_K/M_N</math></b>	3.6
<b>J 10<sup>-3</sup> kgm<sup>2</sup></b>	6.1
<b>Mb max Nm</b>	40(75) <sup>2</sup>
<b>zL 1) c/h</b>	1000
<b>kg</b>	36.9

## Mechanical Data

<b>Design</b>	ALUMINIUM
<b>Degree of protection</b>	IP 55
<b>Bearings DE/NDE</b>	6306/2Z
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device horizontal</b>	permanent lubrication
<b>Regreasing device vertical</b>	permanent lubrication
<b>Cooling</b>	IC 411
<b>Vibration Level</b>	A (normal)
<b>Noise Lpa db(A)</b>	68

## Electrical Data

<b>Voltage</b>	400V - 50Hz
<b>Connection</b>	?/Y 230/400V or ?/Y 400/690V
<b>Duty type</b>	S1
<b>Thermal protection</b>	na
<b>Insulation class</b>	F
<b>Direction of rotation</b>	bidirectional
<b>Ambient temperature</b>	-20°C / +40 °C
<b>Altitude</b>	1000 m.a.s.l.