

Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1



- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type AMBY 90L BA4 - 1.5 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBY 90L BA
Poles	4
kW	1.5
HP	2
rpm	1400
Mn Nm	10.2
η 50%	77.6
η 75%	77.8
η 100%	77.5
cos Phi	0.78
I_N 400 V	3.6
I_N 380-400 V	3.7
I_A/I_N	5.7
M_A/M_N	2.8

M_K/M_N	3
J 10⁻³ kgm²	3.12
Mb max Nm	40
zL 1) c/h	4750
kg	21.1

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6205/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	49

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.