



Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMBY 100L AA4 - 2.2 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBY 100L AA
Poles	4
kW	2.2
HP	3
rpm	1435
Mn Nm	14.6
η 50%	76.5
η 75%	79.1
η 100%	79.9
cos Phi	0.74
I_N 400 V	5.4
I_N 380-400 V	5.6
I_A/I_N	5.3
M_A/M_N	2.5

M_K/M_N	2.7
J 10 ⁻³ kgm ²	4.83
Mb max Nm	40(75) ²)
zL ¹) c/h	4500
kg	28.1

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6206/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	50

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.