



Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMBY 160L BA4 - 15 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBY 160L BA
Poles	4
kW	15
HP	20
rpm	1465
Mn Nm	98.1
η 50%	88.1
η 75%	89.6
η 100%	88.7
cos Phi	0.84
I_N 400 V	29.0
I_N 380-400 V	29.6
I_A/I_N	8.1
M_A/M_N	2.1

M_K/M_N	2.8
$J \cdot 10^{-3} \text{ kgm}^2$	90
$M_b \text{ max Nm}$	150(250) ²)
$zL^{-1}) \text{ c/h}$	600
kg	133

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6309/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	62

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.