



Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMBZ 100L CA4 - 4 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBZ 100L CA
Poles	4
kW	4
HP	5.5
rpm	1400
Mn Nm	27.3
η 50%	80.8
η 75%	81.8
η 100%	80.4
cos Phi	0.78
I_N 400 V	9.2
I_N 380-400 V	9.3
I_A/I_N	6
M_A/M_N	2.6

M_K/M_N	2.9
$J \cdot 10^{-3} \text{ kgm}^2$	7.24
$M_b \text{ max Nm}$	75
$zL^{-1} \text{ c/h}$	4500
kg	38.4

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6306/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	53

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V or ?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.