



Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMBZ 160M AA4 - 11 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMBZ 160M AA
Poles	4
kW	11
HP	15
rpm	1470
Mn Nm	71.9
η 50%	87.0
η 75%	88.9
η 100%	87.6
cos Phi	0.82
I_N 400 V	22.0
I_N 380-400 V	22.7
I_A/I_N	8.2
M_A/M_N	2.1

M_K/M_N	2.8
$J \cdot 10^{-3} \text{ kgm}^2$	69
$M_b \text{ max Nm}$	150(250) ²)
$zL^{-1} \text{ c/h}$	750
kg	118

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6309/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	62

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.