



Brake Motors - IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type AMS 132S ZA8 - 2.2 kW - 8 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMS 132S ZA
Poles	8
kW	2.2
HP	3
rpm	710
Mn Nm	29.6
η 50%	79.3
η 75%	80.5
η 100%	78.8
cos Phi	0.63
I_N 400 V	6.4
I_N 380-400 V	6.6
I_A/I_N	3.4
M_A/M_N	1.7

M_K/M_N	1.7
J 10⁻³ kgm²	33.7
Mb max Nm	30
zL 1) c/h	2000
kg	55

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6208/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	52

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.