



Single-phase Motors - IE2

**HIGH EFFICIENCY MOTORS - IE2**

- Customisation at all levels



## TECHNICAL DATA

**Motor Type** AMMEHE 63Z AA4 - 0.12 kW - 4 poles - 230V - 50Hz

## PERFORMANCE DATA

<b>Type</b>	AMMEHE 63Z AA
<b>Poles</b>	4
<b>kW</b>	0.12
<b>HP</b>	0.16
<b>rpm</b>	1360
<b>Mn Nm</b>	0.8
<b><math>\eta</math> 100%</b>	59.10
<b>cos Phi</b>	0.99
<b><math>I_N</math> 230V</b>	0.9
<b><math>I_A/I_N</math></b>	2.1
<b><math>M_A/M_N</math></b>	1.8
<b><math>M_K/M_N</math></b>	1.4
<b>J <math>10^{-3}</math> kgm<sup>2</sup></b>	0.34
<b>kg</b>	4.9

## Mechanical Data

<b>Design</b>	ALUMINIUM
<b>Degree of protection</b>	IP 55
<b>Bearings DE/NDE</b>	6202/2Z
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device horizontal</b>	permanent lubrication
<b>Regreasing device vertical</b>	permanent lubrication
<b>Cooling</b>	IC 411
<b>Vibration Level</b>	A (normal)
<b>Noise Lpa db(A)</b>	38

## Electrical Data

<b>Voltage</b>	230V - 50Hz
<b>Connection</b>	230V
<b>Running Capacitor Microf</b>	8
<b>Starting Capacitor Microf</b>	20
<b>Duty type</b>	S1
<b>Thermal protection</b>	na
<b>Insulation class</b>	F
<b>Direction of rotation</b>	bidirectional
<b>Ambient temperature</b>	-20°C / +40 °C
<b>Altitude</b>	1000 m.a.s.l.