



Single-phase Motors - IE2

STANDARD MOTORS

- Customisation at all levels



TECHNICAL DATA

Motor Type

AMM 80Z BA4 - 0.55 kW - 4 poles - 230V - 50Hz

PERFORMANCE DATA

Type	AMM 80Z BA
Poles	4
kW	0.55
HP	0.75
rpm	1390
η 100%	67
cos Phi	0.88
I_N 230V	4
I_N 220-240V	4.2
I_A/I_N	3.2
M_A/M_N	0.5
M_K/M_N	1.8
J 10^{-3} kgm ²	2.41
kg	11.3

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6204/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	48

Electrical Data

Voltage	230V - 50Hz
Connection	230V
Running Capacitor Microf	16
Starting Capacitor Microf	-
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.