



Single-phase Motors - IE2

STANDARD MOTORS

- Customisation at all levels



TECHNICAL DATA

Motor Type

AMME 63Z BA2 - 0.18 kW - 2 poles - 230V - 50Hz

PERFORMANCE DATA

| | |
|--|-------------|
| Type | AMME 63Z BA |
| Poles | 2 |
| kW | 0.18 |
| HP | 0.25 |
| rpm | 2800 |
| η 100% | 58.5 |
| cos Phi | 0.98 |
| I_N 230V | 1.2 |
| I_N 220-240V | 1.3 |
| I_A/I_N | 3.0 |
| M_A/M_N | 1.6 |
| M_K/M_N | 1.8 |
| J 10⁻³ kgm² | 0.14 |
| kg | 5.0 |

Mechanical Data

| | |
|-------------------------------------|-------------------------------|
| Design | ALUMINIUM |
| Degree of protection | IP 55 |
| Bearings DE/NDE | 6202/2Z |
| Lubrication grease | low & high temperature grease |
| Regreasing device horizontal | permanent lubrication |
| Regreasing device vertical | permanent lubrication |
| Cooling | IC 411 |
| Vibration Level | A (normal) |
| Noise Lpa db(A) | 49 |

Electrical Data

| | |
|----------------------------------|----------------|
| Voltage | 230V - 50Hz |
| Connection | 230V |
| Running Capacitor Microf | 6.3 |
| Starting Capacitor Microf | 10 |
| Duty type | S1 |
| Thermal protection | na |
| Insulation class | F |
| Direction of rotation | bidirectional |
| Ambient temperature | -20°C / +40 °C |
| Altitude | 1000 m.a.s.l. |