




Synchronous PM Motors - IE6/IE5

HYPER EFFICIENCY MOTORS - IE6

- IE6 Hyper Efficiency
- The revolution in industrial efficiency
- Power, compactness and efficiency

IE6 

TECHNICAL DATA

Motor Type

IE6 HPS 160 1800 634 30 kW - 1800 rpm - 400V - 50Hz

PERFORMANCE DATA

Type	IE6 HPS 160 1800 634
Rated Speed rpm	1800
Rated Power kW	30
Rated Power HP	40
Rated Torque Nm	159
Peak torque Nm	398
Voltage constant Vs	1.45
Torque constant Nm/A	2.5
B.E.M.F. @ rated speed Vrs	272
Rated current Arms	63.4
Efficiency IE code	IE6
Efficiency η %	96.2
Weight Kg	120

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6310 2Z
Bearings NDE	6310 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE	6310 2Z
Bearings NDE	6310 2Z
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)

Electrical Data

Supply Voltage	400V - 50Hz
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1000 m.a.s.l.
Duty type	S1
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-15°C / +40 °C
Altitude	1000 m.a.s.l.