



AC Three-phase Motors - IE4/IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Reliability and efficiency in a well-designed robust package
- Extensive customization options ensure motors match application needs



TECHNICAL DATA

Motor Type AM 71Z BA2 - 0.55 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AM 71Z BA
Poles	2
kW	0.55
HP	0.75
rpm	2830
Mn Nm	1.9
η 50%	57.0
η 75%	64.0
η 100%	71.0
cos Phi	0.77
I_N 400V	1.5
I_N 380-420V	1.6
I_A/I_N	4.8
M_A/M_N	3.2

M_S/M_N	3.1
M_K/M_N	3.3
J 10⁻³ kgm²	0.37
kg	6.2

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	52

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.