



AC Three-phase Motors - IE4/IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Reliability and efficiency in a well-designed robust package
- Extensive customization options ensure motors match application needs



TECHNICAL DATA

Motor Type

AM 112M BA2 - 5.5 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AM 112M BA
Poles	2
kW	5.5
HP	7.5
rpm	2900
Mn Nm	18.1
η 50%	83.6
η 75%	84.7
η 100%	85.0
cos Phi	0.86
I _N 400V	10.9
I _N 380-420V	11.2
I _A /I _N	7.8
M _A /M _N	3.5

M_S/M_N	3.4
M_K/M_N	3.6
$J \cdot 10^{-3} \text{ kgm}^2$	5.8
kg	27.4

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6306/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	68

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V - ?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.