



AC Three-phase Motors - IE4/IE3/IE2/IE1

STANDARD EFFICIENCY MOTORS - IE1

- Reliability and efficiency in a well-designed robust package
- Extensive customization options ensure motors match application needs



TECHNICAL DATA

Motor Type AM 90S AA8 - 0.37 kW - 8 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AM 90S AA
Poles	8
kW	0.37
HP	0.5
rpm	680
Mn Nm	5.2
η 50%	52.0
η 75%	58.0
η 100%	59.0
cos Phi	0.53
I_N 400V	1.7
I_N 380-420V	1.8
I_A/I_N	2.1
M_A/M_N	1.4

M_S/M_N	1.3
M_K/M_N	1.6
J 10⁻³ kgm²	2.91
kg	11.4

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6205/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	42

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.