




AC Three-phase Motors - IE4/IE3/IE2/IE1

PREMIUM EFFICIENCY MOTORS - IE3/CURUS

- IE3 Premium Efficiency compliant since 2010
- Total reliability and longevity in a well-engineered package
- Enhanced designs to meet today's challenges and market needs

IE3

ENERGY
CLASS C

UL US

UL US

SP

CCC

TECHNICAL DATA

Motor Type

AMPE 160M ZA2 - 15 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPE 160M ZA
Poles	2
kW	15
HP	20
rpm	2940
Mn Nm	48.7
η 50%	91.0
η 75%	91.3
η 100%	91.9
cos Phi	0.89
I_N	26.7
I_A/I_N	9.7
M_A/M_N	4.7
M_S/M_N	3.5

M_K/M_N	4.8
J 10⁻³ kgm²	53.4
kg	88.9

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6309/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	74

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.