




AC Three-phase Motors - IE4/IE3/IE2/IE1

PREMIUM EFFICIENCY MOTORS - IE3/CURUS

- IE3 Premium Efficiency compliant since 2010
- Total reliability and longevity in a well-engineered package
- Enhanced designs to meet today's challenges and market needs

IE3

ENERGY
CLASS C

UL US

UL US

SP

CCC

TECHNICAL DATA

Motor Type

AMPE 71Z BA4 - 0.37 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPE 71Z BA
Poles	4
kW	0.37
HP	0.50
rpm	1410
Mn Nm	2.6
η 50%	73.2
η 75%	76.5
η 100%	77.3
cos Phi	0.70
I_N	1.0
I_A/I_N	3.3
M_A/M_N	2.2
M_S/M_N	2.1

M_K/M_N	2.2
J 10⁻³ kgm²	0.8
kg	6

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	42

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.