



**AC Three-phase Motors - IE4/IE3/IE2/IE1**

**PREMIUM EFFICIENCY MOTORS - IE3/CURUS**

- IE3 Premium Efficiency compliant since 2010
- Total reliability and longevity in a well-engineered package
- Enhanced designs to meet today's challenges and market needs



**TECHNICAL DATA**

**Motor Type**

AMPE 160L CA4 - 18.5 kW - 4 poles - 400V - 50Hz

**PERFORMANCE DATA**

Type	AMPE 160L CA
Poles	4
kW	18.5
HP	25
rpm	1470
Mn Nm	122
$\eta$ 50%	92.0
$\eta$ 75%	92.8
$\eta$ 100%	92.6
cos Phi	0.78
$I_N$	37.0
$I_A/I_N$	7.1
$M_A/M_N$	2.1
$M_S/M_N$	1.9

<b><math>M_K/M_N</math></b>	2.6
<b>J 10<sup>-3</sup> kgm<sup>2</sup></b>	120.7
<b>kg</b>	110

## Mechanical Data

<b>Design</b>	Aluminium
<b>Degree of protection</b>	IP 55
<b>Bearings DE/NDE</b>	6309/2Z
<b>Lubrication grease</b>	low & high temperature grease
<b>Regreasing device horizontal</b>	permanent lubrication
<b>Regreasing device vertical</b>	permanent lubrication
<b>Grease Quantity</b>	-
<b>Cooling</b>	IC 411
<b>Vibration Level</b>	A (normal)
<b>Noise Lpa db(A)</b>	62

## Electrical Data

<b>Voltage</b>	400V - 50Hz
<b>Connection</b>	?/Y 400/690V
<b>Duty type</b>	S1
<b>Thermal protection</b>	na
<b>Insulation class</b>	F
<b>Direction of rotation</b>	bidirectional
<b>Ambient temperature</b>	-20°C / +40 °C
<b>Altitude</b>	1000 m.a.s.l.