




AC Three-phase Motors - IE4/IE3/IE2/IE1

PREMIUM EFFICIENCY MOTORS - IE3/CURUS

- IE3 Premium Efficiency compliant since 2010
- Total reliability and longevity in a well-engineered package
- Enhanced designs to meet today's challenges and market needs

IE3

ENERGY
CLASS
C

UL
US

UL
US

SP

CCC

TECHNICAL DATA

Motor Type

AMPE 71Z BA6 - 0.25 kW - 6 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPE 71Z BA
Poles	6
kW	0.25
HP	0.33
rpm	900
Mn Nm	2.7
η 50%	61.4
η 75%	66.2
η 100%	68.6
cos Phi	0.64
I_N	0.9
I_A/I_N	2.5
M_A/M_N	1.7
M_S/M_N	1.6

M_K/M_N	1.7
J 10⁻³ kgm²	1.2
kg	6.6

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	40

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.