




AC Three-phase Motors - IE4/IE3/IE2/IE1

PREMIUM EFFICIENCY MOTORS - IE3/CURUS

- IE3 Premium Efficiency compliant since 2010
- Total reliability and longevity in a well-engineered package
- Enhanced designs to meet today's challenges and market needs

IE3

ENERGY
CLASS C

UL US

UL US

SP

CCC

TECHNICAL DATA

Motor Type

AMPH 100L AA2 - 3 kW - 2 poles - 460V - 60Hz

PERFORMANCE DATA

Type	AMPH 100L AA
Poles	2
kW	3
HP	4
rpm	3515
Mn Nm	8.2
η 50%	85.8
η 75%	88.1
η 100%	88.5
cos Phi	0.86
I_N	4.9
I_A/I_N	10.5
M_A/M_N	5.6
M_S/M_N	5.3

M_K/M_N	5.3
J 10⁻³ kgm²	4.0
kg	23.6

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6206/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Grease Quantity	-
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	66

Electrical Data

Voltage	460V - 60Hz
Connection	YY/Y 230/460V - ? 460V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.