



AC Three-phase Motors - IE4/IE3/IE2/IE1

HIGH EFFICIENCY MOTORS - IE2/CURUS

- Total reliability and longevity in a well-engineered package
- Extensive customization options ensure motors match application needs



TECHNICAL DATA

Motor Type

AMHE 90L CA2 - 2.2 kW - 2 poles - 400V - 50Hz / 460V - 60Hz

PERFORMANCE DATA

Type	AMHE 90L CA
Poles	2
kW	2.2
HP	3
rpm	2860
Mn Nm	7.3
η 50%	82.5
η 75%	84.0
η 100%	84.0
cos Phi	0.85
I_N	4.4
I_A/I_N	10.1
M_A/M_N	3.5

M_S/M_N	3.2
M_K/M_N	3.7
$J \cdot 10^{-3} \text{ kgm}^2$	1.8
kg	16.0

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6205/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	62

Electrical Data

Voltage	400V - 50Hz / 460V - 60Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.