



AC Three-phase Motors - IE4/IE3/IE2/IE1

TWO SPEED MOTORS

- Reliability and efficiency in a well-designed robust package
- Extensive customization options ensure motors match application needs



TECHNICAL DATA

Motor Type

AMV 100L AA4/2 - 0.5/2.5 kW - 4/2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMV 100L AA
Poles	4/2
kW	0.5/2.5
HP	0.67/3.3
rpm	1430/2840
Mn Nm	3.3/8.4
η 100%	72/73
cos Phi	0.77/0.88
I_N 400V	1.3/5.3
I_N 380-420V	1.4/5.6
I_A/I_N	4.6/5
M_A/M_N	2.2/2.3
J 10 ⁻³ kgm ²	4.6
kg	21.4

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6206/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	66

Electrical Data

Voltage	400V - 50Hz
Connection	DAHLANDER - Y/YY