



Brushless Servo Motors

SERVO MOTORS - PREFERRED

- Speed, precision, control for top performance
- Application oriented: tailor-made service, from design to assistance
- Preferred series: for minimum delivery times



TECHNICAL DATA

Motor Type

B71.20Q 20 Nm - 3000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B71.20Q
Stall torque (Deltat=105°C) Mo Nm	20
Rated speed n rpm	3000
Rated power P _n kW	5.5
Rated torque (Deltat=105°C) Mn Nm	17.5
Peak torque M _{pk} Nm	69
Max speed n _{max} rpm	6600
Moment of inertia J 10 ⁻³ Kgm ²	13.1
Peack torque acceleration a _{pk} rad/sec ²	52672
Thermal time constant T _{th} min	46
Voltage constant k _e V _s	0.94
Torque constant k _t Nm/A	1.63
Resistance phase to phase (20°C) R _w ?	0.65
Inductance phase to phase L _w mH	6.3

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	12.3
Rated current I_n Arms	10.7
Peak current I_{pk} Arms	51.3
Power connector size	7/1
Weight kg	17.5

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6205 2ZC3WT
Bearings NDE	6203 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	8
Voltage	400V
Thermal protection threshold θ_{max} °C	140