



Brushless Servo Motors

ULTRA COMPACT SERVO MOTORS

- Up to 30% increased power density
- Up to 20% reduced dimensions
- Sophisticated design, intended for extreme torque stability and precision



TECHNICAL DATA

Motor Type B64.15U 21.4 Nm - 3000 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B64.15U
Stall torque (Deltat=105°C) Mo Nm	21.4
Rated speed n rpm	3000
Rated power P_n kW	5.5
Rated torque (Deltat=105°C) Mn Nm	17.5
Peak torque M_{pk} Nm	51
Max speed n_{max} rpm	6000
Moment of inertia J 10?? Kgm²	7.3
Thermal time constant T_{th} min	12
Voltage constant k_e V_s	0.94
Torque constant k_t Nm/A	1.63
Resistance phase to phase (20°C) R_w ?	0.90
Inductance phase to phase L_w mH	9.6
B.E.M.F. @ rated speed E_n Vrms	296

Stall current I_o Arms	13.1
Rated current I_n Arms	10.7
Peak current I_{pk} Arms	46.0
Connection type/size	7/1
Weight kg	10.6

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6205
Bearings NDE	6303
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Voltage	400V
Poles	10
Thermal protection threshold θ_{max} °C	140