



Brushless Servo Motors

ULTRA COMPACT SERVO MOTORS

- Up to 30% increased power density
- Up to 20% reduced dimensions
- Sophisticated design, intended for extreme torque stability and precision



TECHNICAL DATA

Motor Type

B64.06U 8.5 Nm - 4500 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B64.06U
Stall torque (Deltat=105°C) Mo Nm	8.5
Rated speed n rpm	4500
Rated power P _n kW	2.9
Rated torque (Deltat=105°C) Mn Nm	6.2
Peak torque M _{pk} Nm	17
Max speed n _{max} rpm	6000
Moment of inertia J 10?? Kgm ²	2.8
Thermal time constant T _{th} min	11
Voltage constant k _e V _s	0.63
Torque constant k _t Nm/A	1.09
Resistance phase to phase (20°C) R _w ?	1.62
Inductance phase to phase L _w mH	14.3
B.E.M.F. @ rated speed E _n Vrms	296

Stall current I_o Arms	7.8
Rated current I_n Arms	5.7
Peak current I_{pk} Arms	24.0
Connection type/size	7/1
Weight kg	6.8

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6205
Bearings NDE	6303
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Voltage	400V
Poles	10
Thermal protection threshold θ_{max} °C	140