



Brake Motors - IE3/IE2/IE1

HIGH EFFICIENCY MOTORS - IE2

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMHEBY 71Z XA2 - 0.37 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMHEBY 71Z XA
Poles	2
kW	0.37
HP	0.5
rpm	2810
Mn Nm	1.3
η 50%	67.5
η 75%	71.6
η 100%	69.5
cos Phi	0.77
I_N	1.0
I_A/I_N	4.7
M_A/M_N	3.6
M_K/M_N	3.6

J 10 ⁻³ kgm ²	0.38
Mb max Nm	3.5(7.5) ²
zL 1) c/h	5000
kg	8.2

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	52

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.