



Brake Motors - IE3/IE2/IE1

HIGH EFFICIENCY MOTORS - IE2

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMHEBY 71Z AA2 - 0.75 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMHEBY 71Z AA
Poles	2
kW	0.75
HP	1
rpm	2865
Mn Nm	2.5
η 50%	75
η 75%	78.1
η 100%	79.4
cos Phi	0.71
I_N	1.9
I_A/I_N	5.2
M_A/M_N	3.1
M_K/M_N	3.1

J 10⁻³ kgm²	0.63
Mb max Nm	7.5
zL ¹⁾ c/h	5000
kg	10

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	52

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.