



Brake Motors - IE3/IE2/IE1

HIGH EFFICIENCY MOTORS - IE2

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMHEBY 71Z AA4 - 0.25 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMHEBY 71Z AA
Poles	4
kW	0.25
HP	0.33
rpm	1390
Mn Nm	1.8
η 50%	67.0
η 75%	71.2
η 100%	68.5
cos Phi	0.77
I_N	0.7
I_A/I_N	3.2
M_A/M_N	1.9
M_K/M_N	2

J 10⁻³ kgm²	0.70
Mb max Nm	3.5(7.5) ²)
zL ¹) c/h	7500
kg	8.1

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6203/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	42

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.