



Brake Motors - IE3/IE2/IE1

HIGH EFFICIENCY MOTORS - IE2

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMHES 100L BA2 - 4 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMHES 100L BA
Poles	2
kW	4
HP	5.5
rpm	2920
Mn Nm	13.1
η 50%	85.2
η 75%	86.4
η 100%	86.1
cos Phi	0.86
I_N	7.8
I_A/I_N	8.2
M_A/M_N	3.3
M_K/M_N	3.8

J 10⁻³ kgm²	6.9
Mb max Nm	13
zL ¹⁾ c/h	900
kg	30.2

Mechanical Data

Design	Aluminium
Degree of protection	IP 55
Bearings DE/NDE	6206/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	66

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V or ?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.