




Brake Motors - IE3/IE2/IE1

PREMIUM EFFICIENCY MOTORS - IE3

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMPEBZ 132S AA4 - 5.5 kW - 4 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPEBZ 132S AA
Poles	4
kW	5.5
HP	7.5
rpm	1460
Mn Nm	35.9
η 50%	90.6
η 75%	91.3
η 100%	89.6
cos Phi	0.84
I_N	10.6
I_A/I_N	8.6
M_A/M_N	2.5
M_K/M_N	3.5

J 10⁻³ kgm²	22.0
Mb max Nm	75(150) ²
zL ¹) c/h	2000
kg	60

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6208/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	59

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V or ?/Y 400/690V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.