




Brake Motors - IE3/IE2/IE1

PREMIUM EFFICIENCY MOTORS - IE3

- Options make motors suitable for either onshore or offshore duties
- Engineered to give high performance with maximum efficiency
- Reliability & durability ensured through total control over component supply chains



TECHNICAL DATA

Motor Type

AMPEBY 80Z CA2 - 1.5 kW - 2 poles - 400V - 50Hz

PERFORMANCE DATA

Type	AMPEBY 80Z CA
Poles	2
kW	1.5
HP	2
rpm	2810
Mn Nm	5.1
η 50%	78.8
η 75%	82.2
η 100%	84.2
cos Phi	0.76
I_N	3.6
I_A/I_N	7.8
M_A/M_N	4.9
M_K/M_N	4.3

J 10⁻³ kgm²	2.15
Mb max Nm	7
zL ¹⁾ c/h	1400
kg	13.9

Mechanical Data

Design	ALUMINIUM
Degree of protection	IP 55
Bearings DE/NDE	6204/2Z
Lubrication grease	low & high temperature grease
Regreasing device horizontal	permanent lubrication
Regreasing device vertical	permanent lubrication
Cooling	IC 411
Vibration Level	A (normal)
Noise Lpa db(A)	60

Electrical Data

Voltage	400V - 50Hz
Connection	?/Y 230/400V
Duty type	S1
Thermal protection	na
Insulation class	F
Direction of rotation	bidirectional
Ambient temperature	-20°C / +40 °C
Altitude	1000 m.a.s.l.